

The Euclid Chemical Company

SPEED CRETE RED LINE

Version 2. REVISION DATE: 09/22/2008 Print Date 09/23/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name Product code	: SPEED CRETE RED LINE : TR5101650
COMPANY	: Euclid Chemical Company 19218 Redwood Road Cleveland, OH 44110
Telephone	: 1-800-321-7628
Emergency Phone:	: U.S. only: 1-800-424-9300 International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation Eyes	:	Dust may irritate nose and throat. Dust irritating to the respiratory tract. Direct contact may cause severe irritation. May cause mechanical irritation or abrasion, and possible chemical burns. May cause temporary injury.
Ingestion	:	May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
Skin	:	May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns. May produce cement dermatitis due to primary irritation from alkaline, hydroscopic and abrasive properties.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Portland cement	65997-15-1	40.0 - 70.0	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0	
Calcium Salt	26499-65-0	10.0 - 30.0	
Clay	NJ TSRN# 51721300-5165P	5.0 - 10.0	
Calcium salt	7778-18-9	1.0 - 5.0	



The Euclid Chemical Company

SPEED CRETE RED LINE

Version 2. REVISION DATE: 09/22/2008 Print Date 09/23/2008

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.

Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other
		disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point Method	:	Not available. Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.Use that which is appropriate to the surroundings.
Hazardous combustion products	:	Not available.
Protective equipment for firefighters	:	Not applicable. Product is not expected to burn.
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An **RPM** Company



The Euclid Chemical Company

SPEED CRETE RED LINE

Version 2. REVISION DATE: 09/22/2008		Print Date 09/23/2008
Respiratory protection	:	Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
Hand protection	:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye protection	:	Wear appropriate eye protection.Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
Skin and body protection	:	Prevent contact with shoes and clothing.
Protective measures	:	Use professional judgment in the selection, care, and use.Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.
Engineering measures	:	Use only in well ventilated areas. Provide maximum ventilation in enclosed areas.Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Portland cement	65997-15-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
Crystalline Silica (Quartz)/	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
0-1-1014	00400.05.0		F	Descriptula for other
Calcium Salt	26499-65-0	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	10 mg/m3	
		ACGIH TWA:	3 mg/m3	Respirable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	10 mg/m3	Inhalable fraction.
		ACGIH TWA:	10 mg/m3	Inhalable fraction.
Clay	1332-58-7	ACGIH TWA:	2 mg/m3	Respirable fraction.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		OSHA TWA:	15 mg/m3	Total dust.
			0	

SPEED CRETE RED LINE

Version 2.

REVISION DATE: 09/22/2008

<u>Chemical Name</u>	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Calcium salt	7778-18-9	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 10 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Inhalable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	:	Powder
Color	:	Gray
Odor	:	Slight
рН	:	Not available.
Vapour pressure	:	Not available.
Vapor density	:	Not available.
Melting point/range	:	Not available.
Freezing point	:	Not available.
Boiling point/range	:	Not available.
Water solubility	:	Slightly soluble
Specific Gravity	:	2.9
% Volatile Weight	:	0.0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Not Applicable.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations. Do not incinerate.

An RPM Company

4/6



Print Date 09/23/2008



The Euclid Chemical Company

SPEED CRETE RED LINE

Version 2. REVISION DATE: 09/22/2008 Print Date 09/23/2008

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

Penn RTK Components NJ RTK Components	:	Portland cement Crystalline Silica (Quartz)/ Silica Sand Calcium Salt Clay Calcium salt Portland cement	65997-15-1 14808-60-7 26499-65-0 NJ TSRN# 51721300-5165P 7778-18-9 65997-15-1
Penn RTK Components	:	Crystalline Silica (Quartz)/ Silica Sand Calcium Salt Clay	14808-60-7 26499-65-0 NJ TSRN# 51721300-5165P
U.S. State Regulations: MASS RTK Components	:	Portland cement Crystalline Silica (Quartz)/ Silica Sand Calcium Salt Calcium salt	65997-15-1 14808-60-7 26499-65-0 7778-18-9
Chemical is listed as an IARC, N Crystalline Silica (Quartz)/ Silica			
Regulatory VOC (less water and exempt solvent) VOC Method 310		: 0 g/l : 0 %	
OSHA Flammability		Not Regulated	
OSHA Status: Considered hazardous based on the following criteria:	:	Irritant Carcinogen	
OSHA Hazardous Components : Portland cement Crystalline Silica (Quartz)/ Silica Calcium Salt Clay Calcium salt		65997-15-1 nd 14808-60-7 26499-65-0 NJ TSRN# 51721300-5165P 7778-18-9	
	:	Acute Health Hazard Chronic Health Hazard	
SARA 311/312 Hazards			



The Euclid Chemical Company

SPEED CRETE RED LINE

Version 2. REVISION DATE: 09/22/2008 Print Date 09/23/2008

 Crystalline Silica (Quartz)/ Silica Sand
 14808-60-7

 Calcium Salt
 26499-65-0

 Clay
 NJ TSRN# 51721300-5165P

 Calcium salt
 7778-18-9

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm: 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum 1 = Slight 2 = Moderate 3 = Serious4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists PEL - Permissible Exposure Limit CERCLA - Comprehensive Environmental Response, Compensation, and RCRA - Resource Conservation and Recovery Act Liability Act DOT - Department of Transportation RTK - Right To Know SARA - Superfund Amendments and Reauthorization Act **DSL - Domestic Substance List** STEL - Short Term Exposure Limit EPA - Environmental Protection Agency HMIS - Hazardous Materials Information System TLV - Threshold Limit Value IARC - International Agency for Research on Cancer TSCA - Toxic Substances Control Act MSHA - Mine Safety Health Administration TWA - Time Weighted Average NDSL - Non-Domestic Substance List V - Volume NIOSH - National Institute for Occupational Safety and Health VOC - Volatile Organic Compound WHMIS - Workplace Hazardous Materials Information NTP - National Toxicology Program System OSHA - Occupational Safety and Health Administration